

Main Board	VariPOS 715			COM3 : RJ-48 for VFD, RS-232, Pin10 w/RI/5V/12V Selectable by BIOS	COM3/4 : RJ-48 , RS-232, Pin10 w/RI/5V/12V Selectable by BIOS
CPU	Intel® Pineview D410 (Single Core) 1.66GHz with L2 Cache 512KB			COM4 : DB-9, RS-232, Pin9 w/RI/5V/12V Selectable by BIOS (Optional)	
	Intel® Pineview D510 (Dual Core) 1.66GHz with L2 Cache 1MB		Audio Port	1 x Line-out ; 1 x Mic-In(Optional)	1 x Line-out ; 1 x Mic-In
			Power Switch	1 x Power Switch(Optional)	1 x Power Switch
			PS/2 Port	1 x PS/2 connector for Keyboard	1 x PS/2 connector for Keyboard (optional)
			LPT Port	1 x DB-25 Printer Port (Standard)	1 x DB-25 Printer Port (Standard)
Chipset	Intel® Pineview + ICH8M		VGA Port	1 x DB-15 VGA Port (Optional)	
System Memory	1 x SO-DIMM DDRII 667, up to 2GB		Card Reader & iButton	COM5 : Internal Pin header for Card Reader & iButton	
Display			Audio	HD Audio, 2W Speaker x 2	
TFT LCD	38.1cm (15")		Bus Expansion	1 x Mini-PCI-E Slot	
Brightness	250nits		Compliance	IP 66 on front panel	
Resolution	1024 x 768		OS Support	Windows 7, Windows POSReady 2009, WEPOS, Windows XP Pro for Embedded, Fedora(Linux)	
Touch Screen	True Flat Projected Capacitive Technology / True Flat 5-Wire Resistive		Power Supply	External adapter, DC Model:80 Watts, Voltage:+12VDC 6.6 Amax	External adapter, DC Model:120 Watts, Voltage:+12VDC 10 Amax
Storage			Material	Main Unit: Die-casting aluminum ; I/O Cover:Plastic	
HDD / SSD Type	1 x SATA 6.4cm (2.5")HDD , SSD (optional)		Color	Main Unit: Gray / White / Black *Customized color for plastic parts	
Compact Flash Type	1 x Slot Type II	N/A	Certifications	CE, FCC, Class-A, RoHS, WEEE	
I/O Ports -External			Dimension(W x H x D)	370 x 300x 236 mm	
DC Input	1 x Mini Din 4P (DC 12V only)		Weight	5.68 Kg (Aluminium Base: 1 Kg)	
Cash Drawer	1 x RJ-11 (Power Pin 12V)		VESA Mounting	100 x 100mm	
Network (LAN)	1 x Gigabit Ethernet by RJ-45		Operating Temperature	0°C ~ 40°C, 10% ~ 90% RH, non-condensing	
USB Port	4 x USB 2.0		Storage Temperature	-20°C ~ 60°C, 10% ~ 90% RH, non-condensing	
Serial Port	4 x RS-232	4 x RS-232			
	COM1/2 : DB-9, RS-232, Pin9 w/RI/5V/12V Selectable by BIOS				

* The right has been reserved to change the specification without prior notice.